

Dust Masks

Ideal for Insulation-Blowing Pros



www.x-floc.com



Professional dust mask:

- ▶ Protects mouth, eyes and nose
- ▶ Enables a more fluid work flow when working in very dusty conditions
- ▶ Increases personnel motivation
- ▶ Promotes better project results



	EA3000 (Prod.No. 8318)	Proflow (Prod.No. 3709)
Recommended use	Safe work in environments with particle loads	For excellent everyday working comfort and difficult working conditions
Total weight Ready-Pack	1,8 kg	2,1 kg
Blower Unit		
Certification	EN12941 - CE0086	EN12941, EN12942, CE0121
Operating time	up to 9 h	7...15 h
Battery	Li-Ionen-Akku	NiMH 9,6V
Area of application	Blow-in of loose-fill insulation in dusty area (BGR 190 (ZM1/701); BGI 504-26 (ZH1/600.26))	
Charging time	6 h	6 h
Display	button with LED-display (red+green)	Digital LED-display (red+green)
Warning signal (visual + acoustical)	Status display, battery display, alarm status (small amount of airflow, low battery charge)	Obstruction the air flow, battery status and filter saturation
Air power	160l/min (auto. adjustment)	120 l/min (regulated)
Volume of the blowers in during operation	70 dB	65 dB
Shock-resistant case	✓	✓
Environmental humidity in the application	< 75 %	< 75 %
Air humidity filter	< 75 % (P3-particle filter)	< 75 % (P3-particle filter)
Number of filter	2 filter	2 filter
Operating temperature	-10°C...+50°C	-10°C...+50°C
Strap	Size adjustable hip strap with plastic clasp	Size adjustable hip strap with plastic clasp and padded back panel
Mask		
Material	PVC-hood according to EN 166 B Optional: coated hardness, solvent-resistant, scratch-proof visor	
Target protection class	TH3	TH2P
Hood weight	240 g	240 g
Contents	Respiratory protection blower, standard belt, face shield with anti-fogging viewing glass, face seal and wide elastic headband, breathing hose with bajonet catch, 2x particle filters incl. prefilter sets, rechargeable battery incl. charging cradle, charger and several connectors	Breathing protection blower, PF2-SC; Automask safety mask with scratch proof visor; rechargeable battery; neoprene hose; comfortable belt; elec. charging device; P3 filter; pre-filter holder, 1 pack of pre-filters

For prices, see current price list - Published 02.2019 - We accept no responsibility for errors or changes.

X-Floc Dämmtechnik-Maschinen GmbH | Rosine-Starz-Straße 12 · 71272 Renningen · Germany | Telephone + 49 - 7159 - 80470 - 30 · Fax - 40 | www.x-floc.com